



FiberLink® 3355 Series



3G/HD/SD-SDI to DVI Optical Receiver

**Installation and Operations
Manual**

Contents

Welcome	3
Features	3
Package Contents	3
Technical Specifications	
Model Part Number Specifications	4
General Specifications	4
Installation Instructions	6
Audio Pair Selection	7
Indicator LEDs	7
Application Diagrams	8
Operating Pointers	9
Troubleshooting	9
Maintenance and Repairs	10
Certifications	10

Welcome

Thank you for purchasing Artel Video Systems' FiberLink 3355 Series. The 3355 Series is used to convert 3G/HD/SD-SDI with or without embedded audio transmitted over a single fiber optic core to DVI. The FiberLink 3355 Series is compatible with single mode or multimode fiber. The 3355 is also compliant with SMPTE 297-2006 for seamless interoperability with other SMPTE 297-2006 devices. The system delivers noise-free transmission that retains all of the signals' initial parameters, regardless of fiber optic cable attenuation. The 3355 Series also provides immunity to video pathological signals over the entire link budget and operating temperature range.

Features

- Convert 3G/HD/SD-SDI with embedded audio to DVI with audio pair selection
- Supports all SD and HD resolutions to 1080p/60
- Fully SMPTE 297-2006 compliant fiber input
- Stereo line level outputs (if audio present in SDI stream)
- Re-clocked SDI BNC output allows for continuous 3G/HD/SD-SDI signal distribution
- User selection from up to 8 audio channel pairs for multilingual or multmessage support
- Automatic selection of output resolution - no scaling
- ST and LC fiber connector options
- Small compact design
- Compatible with FiberLink 3350, 3360 & 3380 Series and Scan Do® HD's optical output.

Package Contents

- One FiberLink 3355
- This User's Manual

Technical Specifications

Model Part Number Specification

Unit Type	Part Number
Receiver Box	3355-B7L (LC) 3355-B7S (ST)

General Specifications

Indicators	Power, Alarm, Data Rate Lock (3G, HD, SD)
Box Version Dimensions	6.5 W x 1.15 H x 6 L (inches) 165 W x 29 H x 152 L (mm)
Weight	16 ounces, 453.5 grams
Power	9-24 volts, AC or DC, 5.5 watts
Operating Temperature	-10° C to +50° C

Fiber Optic Input

SMPTE 297-2006 Labeling	PC-ABCD-1310-1550
Connector	LC receptacle, PC polish or ST
Wavelength	1100 - 1620 nm
Minimum Input Sensitivity	-17 dBm at 2.97 Gbps; -20 dBm at 1.485 Gbps -23 dBm at 270 Mbps;
Maximum Input Power	0 dBm

Video Output

Number of Outputs	1
Connector Type	DVI Female
Signal Format	Single link DVI, RGB or YCrCb as negotiated with display
Resolutions Supported	All 3G/HD/SD-SDI formats from standard definition to 1080p/60
3G/HD/SD-SDI Output	Standard, Follows fiber optic input
HDCP Compliant	Yes. SDI signals, by definition, are not encrypted

Technical Specifications

Audio Output

Optical Input

Number of Audio Channels	2 channels, unbalanced, line level
Audio Connector	RCA Jacks
Switches	Front panel selection of one of 8 audio channel pairs on SDI signal to output

3G/HD/SD-SDI Output

Signal Level	800mV \pm 10%
DC Offset	0V \pm 0.5V
Rise/Fall Time	< 135 ps at 2.97 Gbps per SMPTE 424M; < 270 ps at 1.485 Gbps per SMPTE 292; 0.4 ns to 1.5 ns at 270 Mbps per SMPTE 259M
Overshoot	< 10% of amplitude
Timing Jitter	< 0.2 UI at 270 Mbps; < 1.0 UI at 1.485 Gbps; < 2.0 UI at 2.97 Gbps with color bar signal
Alignment Jitter	< 0.2 UI at 270 Mbps; < 0.2 UI at 1.485 Gbps; < 0.3 UI at 2.97 Gbps with color bar signal
Re-clocking	At 270 Mbps, 1.485 Gbps & 2.97 Gbps

Installation Instructions


The FiberLink 3355 Series of fiber optic transmission systems are ready for immediate use and do not require any special tools. However, an Optical Power Meter, such as the FiberLink 6615, can be useful in determining optical loss budgets during your systems design and maintenance.

FiberLink 3355 will operate with the FiberLink 3350, FiberLink 3360, FiberLink 3370, FiberLink 3380, Scan Do[®] HD, FiberLink Matrix and SMPTE 297-2006 compliant optical transmission units. The following procedure presumes you have followed the instructions for installing your optical transmitter unit.

The following instructions describe the typical installation procedure:

- 1) Connect the fiber optic cable to the optical input of the receiver unit.
- 2) Connect the video output cable (DVI) to the video output DVI connector on the receiver unit.
- 3) Optionally connect any audio cables and using the channel pair rotary selector, choose your desired audio output channel. Audio is also embedded on the DVI cable.
- 4) Terminate any unused BNC output connector at 75 Ohms.
- 5) Connect the Universal Power Supply to the transmitter and receiver units. Please refer to figure 1.
- 6) When power is applied, the green POWER LED should illuminate, indicating the presence of operating power. The 3G/HD/SD RATE LED will give an indication as described in the Indicator LED's and Alarm Circuitry section of this manual.
- 7) The system should now be operational.

Figure 1:
Power Connector
DC Input Polarity



The transmitting element in the FiberLink 3350, 3360, 3370 and 3380 transmitter units contains a solid state Laser Diode located in the optical connector. This device emits invisible infrared electromagnetic radiation which can be harmful to human eyes. The radiation from this optical connector, if viewed at close range with no fiber optic cable connected to the optical connector, may be sufficient intensity to cause instantaneous damage to the retina of the eye. Direct viewing of this radiation should be avoided at all times!

DANGER!

Audio Pair Selection

The FiberLink 3355 Series has a rotary dial switch that allows you to select which audio pair to output. The chart below describes the operation of the rotary switch positions:

Rotary Switch Positions

Position	Function
0	Will mute the audio output
1 through 8	Will output the respective audio channel pair on the DVI cable and the audio output connectors
9	Not used




Indicator LEDs

The FiberLink 3355 Series has six integral indicator LEDs that are used to monitor the state of the unit.

Receiver LEDs

LED	Status	Definition
Power	On	Indicates that correct power has been applied.
3G Rate	Off On	Indicates no 3G-SDI data rate lock Indicates 3G-SDI data rate lock at 2.97 Gbps or 2.97/1.001 Gbps
HD Rate	Off On	Indicates no HD-SDI data rate lock Indicates HD-SDI data rate lock at 1.485 Gbps or 1.485/1.001 Gbps
ED Rate	Off On	Indicates no ED resolution data rate lock Indicates ED resolution data rate lock at 540 Mbps
SD Rate	Off On	Indicates no SD-SDI or DVB-ASI data rate lock Indicates SD-SDI or DVB-ASI data rate lock at 270 Mbps
Alarm	On	Loss of optical signal or the DVI display does not support the resolution being used. Computer monitors do not support interlaced video.

Note: The 3G, HD, ED and SD LEDs indicators are off when a non-standard signal is applied.



Operating Pointers

Remember to check attenuation of the fiber optic cable. The system will only operate properly if these specifications fall within the range of the system's loss budget.

Note: If no signal is applied to the 3355 Transmitter, no optical power will be present on the 3355 Transmitter's output.

Troubleshooting

Multimode fiber optic cable contains an optical fiber with a light carrying "core" that is only .0025 inches (62.5 microns) in diameter. Single mode fiber optic cable has an even smaller "core," only .00032 to .0004 inches (8-10 microns). This is smaller than a human hair! Therefore, any minute particles of dirt or dust can easily block the fiber from accepting or radiating light. To prevent this from happening, always use the provided dust caps when ever optical connectors are exposed to air. It is also a good idea to gently clean the tip of an optical connector with a lint-free cloth moistened with alcohol whenever dust is suspected.

The status of the LEDs should provide the first clue as to the origin of any operational failure. If these are off, it usually means that the fiber is broken or has too much attenuation. Next, be certain that the input and output signal connections are correct.

An optical power meter, such as the FiberLink 6615, a visible light source, such as the FiberLink 6610, and a Three Wavelength Light Source, such as the FiberLink 6620, can greatly assist and expedite troubleshooting of fiber optic transmission systems and are recommended tools all installers should have available.

Finally, although multimode and single mode devices may look the same, they will not operate properly together. Using the wrong device or fiber can easily add more attenuation than specified, resulting in poor overall performance. It should be noted that some of our fiber optic products support both single mode and multimode fiber in the same unit.

If, after reviewing the above possibilities, the system is still not operating, please contact the Customer Service Department for further assistance. If you suspect your problem is caused by the optics or the fiber optic cable, and you have an optical power meter, please take the appropriate measurements prior to contacting support.

Maintenance and Repairs

The FiberLink 3355 Series has been manufactured using the latest semiconductor devices and techniques that electronic technology has to offer. They have been designed for long, reliable and trouble-free service and are not normally field repairable.

Should difficulty be encountered, Artel Video Systems maintains a complete service facility to render accurate, timely and reliable service of all products.

The only maintenance that can be provided by the user is to ascertain that optical connectors are free of dust or dirt that could interfere with light transmission and that electrical connections are secure and accurate. Please see the Troubleshooting section of this manual for additional information.

An optical power meter, such as the FiberLink 6650, a visible light source, such as the FiberLink 6656, and a Three Wavelength Light Source, such as the FiberLink 6654, can greatly assist and expedite troubleshooting of fiber optic transmission systems and are recommended tools all installers should have available.

All other questions or comments should be directed to our Customer Service Department. It should be noted that many "problems" can easily be solved by a simple telephone call.

If you suspect your problem is caused by the optics or the fiber optic cable, and you have an optical power meter, please take the appropriate measurements prior to contacting support.

Certifications



Proven Products, Unrivalled Service, and Great Support



- High performance plug and play products
- Stand alone and card cage versions available
- Solutions for most video, audio, and data formats
- Multimode and single mode versions
- Designed and manufactured in the USA
- Training and installation support available
- 24x7x365 technical support available



Artel Video Systems Corp.
5B Lyberty Way,
Westford, MA 01886 USA
T: 978-263-5775
F: 978-263-9755
sales@artel.com
customercare@artel.com
www.artel.com

All specifications subject to
change without notice. ©2016
Updated 07/31/2016
CS200-129070-00_H